



<b>Product code</b>	61 00 50 (including stand and filter)
<b>Product description</b>	Compressed air filter station (removes solid particles, oil mist and unpleasant odours which are present in the compressed air distribution system thereby providing the conditions necessary to meet the standards EN 12021)
<b>Inlet connection</b>	RECTUS 25, 26 and CEJN 320
<b>Outlet connection</b>	RECTUS 25, 26 and CEJN 320
<b>Inlet pressure</b>	300 - 1 000 kPa
<b>Weight</b>	6 800 g (including filter)
<b>Dimensions</b>	240 mm / 380 mm / 220 mm
<b>Materials</b>	Steel - powder-coated finish
<b>Recommended inlet hose type</b>	61 00 30 - Pressure hose standard (Rectus 25, 26 or CEJN 320) Length: 10 m
<b>Recommended outlet hose type</b>	61 00 46 - Pressure hose spiral (Rectus 25, 26 or CEJN 320) Length: 10 m
<b>Storage conditions</b>	+10 °C to + 60 °C, humidity 20 - 80 % RH
<b>Operating conditions</b>	0 °C to + 45 °C, humidity 20 - 80 % RH

#### Product sets / variations

product code	product description
61 00 50	CA Conditioner with stand including filter

#### Spare parts and accessories

product code	product description
61 00 30	Pressure hose standard 10 m
61 00 38	Pressure hose standard 25 m
61 00 39	Pressure hose standard 50 m
61 00 46	Pressure hose spiral 10 m
61 00 10	Filter for CA Pressure Conditioner

#### Areas of application

CleanAIR® Pressure Conditioner in combination with CleanAIR® Pressure (Flow Master) and an appropriate headtop can be used in various application including: dusty industrial environments, automotive industry, shipbuilding industry, welding, grinding, surface finishing operations, building industry and agriculture.

#### Limitations



- Please, read carefully relevant instruction for use and follow your national safety regulations for PPE.