

Product code

56 00 10

Description

CleanAIR® Filter P R SL was developed specially for combinations with the unit CA Asbest. It provides protection against particles in the form of liquid and solid aerosols e.g. dust, smoke, metal fumes, mists, fibers, bacteria and viruses.



Standards

TM3 P R SL according to **EN 12942:1998 / A2:2008**

Compatibility

CleanAIR® Filter P R SL is developed for using with the unit CleanAIR® Asbest.

Pressure drop

130 Pa

Weight

101 g

Dimensions

diameter 110 mm
height 57 mm

Materials

filter housing: ABS
filtration medium: microfiber glass media

Thread

diameter 50 mm, thread pitch 4 mm

**Storage conditions
Operating conditions**

-10°C to + 55°C, humidity 20 - 80 % RH
+10°C to + 40°C, humidity 20 - 80 % RH

REQUIREMENTS EN 12942:1998 / A2:2008	
Breathing resistance during the test with: Shigematsu GX02 full face mask and the unit CleanAIR® Asbest	
unit switched on	max. 350 Pa
unit switched off	max. 1 100 Pa
Initial penetration during the clogging test	
Sodium Chloride NaCl	max. 0,05 %
Paraffin oil	max. 0,05 %

At all circumstances, the manufacturer can guarantee that the filters comply with required standards.

Limitations



- Please, read carefully relevant instruction for use and follow your national safety regulations for PPE.
- Disposal should be undertaken in accordance with local environmental, health and safety regulations.