

Product code

71 01 00

Product description

Short hood

StandardsEN 12941 TH2,
EN 14594 3A**Protection of respiratory tract**

when used with:

- CleanAIR® PAPR systems provides level of protection up to TH2 according to EN 12941
- CleanAIR® compressed air line systems provides level of protection 3A according to EN 14594

Weight

180 g

Product dimensions

150 mm / 350 mm / 300 mm

Visor dimensions

270 x 150 mm

Colour

orange / blue

Materials

Hood - polyester with PVC coating
Hose connector / Exhalation valve - ABS
Headband - polyamid PA6
Visor - plasticized cellulose propionate
Canvas - synthetic leather

Recommended hose type

70 00 60 - Light flexi hose
Internal thread CA40x1/7" - external thread CA40x1/7"
Lenght: seft adjusting: 600 mm - 1 100 mm / Weight: 150 g

Storage conditions

-10°C to + 55°C, humidity 20 - 80 % RH
avoid long exposure of UV radiation

Operating conditions

+10°C to + 40°C, humidity 20 - 80 % RH

Product sets / variations

| product code | product description |
|--------------|--------------------------|
| 71 01 00 | Short hood CA-1 - orange |
| 71 01 00B | Short hood CA-1 - blue |

Spare parts and accessories

| product code | product description |
|--------------|---|
| 70 00 60 | Light flexi hose CA40x1/7"- CA40x1/7" - straight connector |
| 70 00 60B | Light flexi hose CA40x1/7"- bayonet - straight connector |
| 70 00 86CA | Rubber hose CA40x1/7"- CA40x1/7" - straight connector |
| 70 00 86B | Rubber hose CA40x1/7"- bayonet - straight connector |
| 70 01 20 | Protection plate [suitable for CA-1, CA-2 and CA-10 - 10 pcs] |
| 16 70 01 | Sweatband CleanAIR® |
| 71 01 10 | Winter cap + sweatband |

Compatible respiratory units (According to EN 12941)

| product code | product description | level of protection |
|--------------|--------------------------------|---------------------|
| 30 00 00PA | CleanAIR® AerGO® | TH2 |
| 51 00 00FCA | CleanAIR® Chemical 2F | TH2 |
| 52 00 00FCA | CleanAIR® Chemical 3F | TH2 |
| 80 00 00XPA | CleanAIR® Basic 2000 DF | TH1 |
| 82 00 00PA | CleanAIR® Basic 2000 FC | TH2 |
| 67 00 00 | CleanAIR® Pressure Flow Master | 3A |
| 63 00 00 | CleanAIR® Pressure | 2A |

[According to EN 14594]

Areas of application

Short hood CA-1 consist of chemically resistant visor and an integrated air distribution system. The adjustable headband ensures perfect fitting (the head circumference and height are adjustable in three levels). The size of the hood can be adjusted at two points - on the neck and scruff. The wide panoramatic visor enables good orientation and has a special anti-fog coating.

Short hood CA-1 provides sufficient protection of the breathing paths and protect the foreface against splashing of dangerous fluids.

Short hood CA-1 finds application in dusty enviroments without the necessity to protect neck and shoulders and enviroments with low chemical resistance requirements.

Limitations



- Please, read carefully relevant instruction for use and follow your national safety regulations for PPE.