

TECHNICAL DATASHEET



WWW.CLEAN-AIR.CZ

CleanAIR® Chemical 3F Plus

Powered air purifying respirator



Description

The battery-powered air purifying respirator (PAPR), the breathing protective device for increasing comfort and safety when combined with approved headtops.

Application

In default Chemical 3F Plus provides protection against particulates, but is also capable to provide protection against wide range of contaminants when used with combined filters.

TECHNICAL DATASHEET

CleanAIR® Chemical 3F Plus

Powered air purifying respirator



Technical specification

Product code	52 00 00FCA		
Flow rate	Airflow [lpm]	Mode	Filter category
	120 / 140 / 160	Mask EN 12942	Particle
	120 / 140 / 160		Light combined (class 1)
	120 / 140 / 160		Heavy combined (class 2)
	160 / 185 / 210 / 235	Hood EN 12941	Particle
	160 / 185 / 210 / 235		Light combined (class 1)
160 / 185 / 210	Heavy combined (class 2)		
Battery	Standard battery		
Voltage	14,4 V		
Capacity	2,6 Ah		
Charging time	< 3 hours		
Operation time*	< 10 hour*		
Battery lifespan	up to 500 charging cycles		
Battery charger	Microprocessor controlled, fully automatic Input: 100 - 240 V (50/60 Hz) Output: 18 V (max. 1 500 mA) Available plugs: EUR, UK and AUS		
Weight	1 100 g (including standard battery)		
Dimensions	320 mm / 200 mm / 150 mm (with standard battery)		
Noisiness	< 62 dB		
Materials	Unit: high performance polyamide Belt: textile part - polyester/nylon/rubber foam plastic part - polyamide		
Motor	Ball-bearing brushless motor		
Input / Output (threads)	Filter thread - RD40x1/7" - 2x Airflow output thread - CA40x1/7" - 1x		
Belt - waist size:	Comfort padded belt - up to 1 500 mm		
Display	TFT display (262k colours, 160x160 px) (showing actual working mode, airflow, filter condition and battery status)		
Standard	EN 12941	EN 12942	
Protection class / NPF***	TH3 / 500	TM3 / 2000	
Storage conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh		
Operating conditions	0°C to + 60°C, humidity 20 - 95 % Rh		

* with new P3 filters and fully charged battery / ** depends on used headtop

** with input and output threads closed with CleanAIR® plugs (product code: 51 00 46)

Features

Warning system - visual, audible and vibrating warning for low airflow and low battery charge.

Flow control system - maintains level of airflow constant regardless filter clogging or battery charge.

Automatic closing system - reduces the risk of unwanted contamination of the unit while the filters are being changed

Allows immersion disinfection - with input and output threads plugs on (Sodium hypochloride or Persteril).

LED display - LED display visualises airflow, filter clogging and battery charge.

TECHNICAL DATASHEET

CleanAIR® Chemical 3F Plus

Powered air purifying respirator



Product sets / variations

52 00 00FCA	Powered air purifying respirator 3F, exchangeable battery, charger (EURO - plug), comfort padded belt, flow indicator
52 00 00FDA	Powered air purifying respirator 3F, exchangeable battery, charger (EURO - plug), decontaminable belt, flow indicator

* Add U or AUS to the end of product code for ordering charger with UK or AUS plug

Spare parts and accessories

52 00 10	Battery Li-Ion 14,4 V / 2,6 Ah
52 00 43.1	Comfort padded belt
51 00 41	Decontaminable belt
51 00 42	Decontaminable harness
52 00 44.1	Comfort padded harness
70 00 60	Light flexi hose CA40x1/7"- CA40x1/7" - straight conn.
70 00 86CA	Rubber hose CA40x1/7"- CA40x1/7" - straight connector
71 00 62F	Hose cover flameproof
70 00 62C	Hose cover chemical resistant
51 00 30EUR	Charger Li-Ion 14,4 V - EURO
51 00 30UK	Charger Li-Ion 14,4 V - UK
51 00 30AUS	Charger Li-Ion 14,4 V - AUS
52 00 46	Set of plugs (3x external thread, 1x internal thread) for decontamination of unit 3F
52 01 01	TFT display protective foil

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

TECHNICAL DATASHEET

CleanAIR® Chemical 3F Plus

Powered air purifying respirator



Compatible headtops

72 01 02B	Short protective hood CA-1, blue	TH3
72 01 02	Short protective hood CA-1, orange	TH3
72 01 12	Short protective hood CA-1+, orange	TH3
72 01 12B	Short protective hood CA-1+, blue	TH3
72 02 02B	Long protective hood CA-2, blue	TH3
72 02 02	Long protective hood CA-2, orange	TH3
72 10 02	Chem-proof protective hood CA-10	TH3
72 03 00.01	Protective face shield UniMask, grey	TH3
72 03 00.02	Protective face shield UniMask, blue	TH3
72 03 00.03	Protective face shield UniMask, orange	TH3
72 03 00.04	Protective face shield UniMask, red	TH3
72 03 00.08	Protective face shield UniMask, neoprene	TH3
71 03 00	Grinding shield CA-3 (polycarbonate visor)	TH2
71 03 01	Grinding shield CA-3 (acetate visor)	TH2
71 04 01*	Safety helmet CA-4 orange face seal	TH2
71 04 03*	Safety helmet CA-4 additional flip-up visor, earmuffs, orange face seal	TH2
70 40 01	Safety helmet CA-40 weld. shield, ADF V9-13 DS	TH3
70 41 00	Safety helmet CA-40G grinding shield	TH3
70 42 01	Safety helmet CA-40GW grinding + welding shield, ADF V9-13 DS	TH3
70 20 70	Welding hood CA-20 ADF V9-13 DS	TH3
70 20 81	Welding hood CA-20 ADF V6-8/9-13 GDS	TH3
70 29 01	Welding hood CA-29 Evolve ADF V9-13 DS	TH2
70 05 00	Half mask CA-5 Eurmask DIN	TM2
71 06 00	Full face mask GX02, size [S, M, L]	TM3
72 06 00	Full face mask CF02, size [M, L]	TM3

* for ordering blue face seal please add „B“ at the end of the product code

** for ordering variant with „Flexi“ seal, please add „F“ at the end of the code

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

TECHNICAL DATASHEET

CleanAIR® Chemical 3F Plus

Powered air purifying respirator



Compatible filters

Product code:	Product name	P-white	A-brown	AX-brown	B-grey	E-yellow	K-green	Hg-red	Ozone (10 ppm)	EN 14387	EN 143	EN 12941	EN 12942	EN 148-1 (RD40x1/7")	Note:
Combined filters, thread RD40*1/7"															
50 03 57	A1P3	✓	✓									✓	✓	✓	-
50 01 57	A2P3	✓	✓							✓		✓	✓	✓	-
50 01 62	B2P3	✓			✓				✓	✓		✓	✓	✓	-
50 01 60	K2P3	✓				✓			✓	✓		✓	✓	✓	-
50 01 67	A2B2P3	✓	✓		✓				✓	✓		✓	✓	✓	-
50 01 64	A2B2E2P3	✓	✓		✓	✓			✓	✓		✓	✓	✓	-
50 03 64	A1B1E1P3	✓	✓		✓	✓						✓	✓	✓	-
50 01 68	A2B2E2K2P3	✓	✓		✓	✓	✓		✓	✓		✓	✓	✓	-
50 01 65X	NBC - A2B2E2K2P3	✓	✓		✓	✓	✓			✓		✓	✓	✓	NBC filtr
50 01 66	A2B2E2K2HgP3	✓	✓		✓	✓	✓	✓	✓	✓		✓	✓	✓	max. 50 hours
50 02 57	A2P - ZERO	✓	✓							✓		✓	✓	✓	two-thread filter
50 02 66	A2B2E2K2HgP - ZERO	✓	✓		✓	✓	✓	✓	✓	✓		✓	✓	✓	two-thread filter
50 02 68	A2B2E2K2P - ZERO	✓	✓		✓	✓	✓		✓	✓		✓	✓	✓	two-thread filter
Particle filters, thread RD40*1/7"															
50 00 48	P3	✓									✓	✓	✓	✓	-
50 02 49	ZERO	✓									✓	✓	✓	✓	two-thread filter
50 40 48	P3 lite	✓									✓	✓	✓	✓	-
50 42 49	ZERO lite	✓									✓	✓	✓	✓	two-thread filter

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.