

CleanAIR® Pressure Conditioner

High capacity combined filter



Description

CleanAIR® Conditioner contains the high capacity combined filter that removes solid particles, oil mist and unpleasant odours out of the air line system.

Application

Can be used in combination with CleanAIR® Pressure [Flow Master] and improve the quality of the air flowing into the headtop.

TECHNICAL DATASHEET

CleanAIR® Pressure Conditioner

High capacity combined filter



Technical specification

Product code	61 00 50
Weight [including filter]	6 800 g
Dimensions	240 mm / 380 mm / 220 mm
Inlet connection	RECTUS 25, 26 and CEJN 320
Outlet connection	RECTUS 25, 26 and CEJN 320
Inlet pressure	300 - 1 000 kPa
Materials	Steel - powder-coated finish
Recommended inlet hose	61 00 30 - Pressure hose standard (length: 10 m)
Recommended outlet hose	61 00 46 - Pressure hose spiral (length: 10 m)
Storage conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh
Operating conditions	0°C to + 60°C, humidity 20 - 95 % Rh

Compatible accessories and spare parts

Product code

Pressure hose standard 10 m	61 00 30
Pressure hose standard 25 m	61 00 38
Pressure hose standard 50 m	61 00 39
Pressure hose spiral 10 m	61 00 46
Filter for CA Pressure Conditioner	61 00 10

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.