* the picture is ilustrational only and may vary depending on additional equipment

TECHNICAL DATASHEET



CleanAIR® CA-23

Welding helmet with air distribution



Description

Welding hood with the air distribution and automatic welding filter.

Application

Suitable for most welding methods including TIG. Ideal for occasional welders, maintenance workers, carriage builders and building assemblers



DA-063_-_702360_-_CA-23_-_EN

Revision.: 2020_01_17 Output.: 2020_01_17

© CleanAIR® All rights reserved

TECHNICAL DATASHEET

CleanAIR® CA-23

Welding helmet with air distribution



Technical specification	
Product code	70 23 60
Weight	700 g
Dimensions	330 mm / 225 mm / 290 mm
Autodarkening filter	ADF Balder SQ 9-13 Dimensions 110 x 110 mm Viewing area 95 x 45 mm
Materials	Safety helmet - Polyamide (Zytel) Welding shield - Polyamide (Zytel)
Input (threads)	QuickLOCK™
Colour	Black
Standard / Protection class	EN 12941 TH2
Storage conditions Operating conditions	- 10°C to + 55°C, humidity 20 - 95 % RH + 10°C to + 40°C, humidity 20 - 95 % RH
Recommended hose type	Light flexi hose QuickLOCK™ - CA40x1/7" (71 00 60)

Compatible powered air purifying respirators

CA Basic EVO including comfort belt, multi plug (EUR, UK, US, AUS) battery charger Li-Ion battery, particle filter and flow indicator

Product code: 70 23 60



Compatible accessories and spare parts		
Assembly kit for welding hood includes face seal, air duct, sweatbands 2 pcs	44 00 85CA	
Face seal for welding hood – universal	70 21 53	
Light flexi hose QuickLOCK™ - CA40x1/7"	71 00 60	
Front frame CA-23	70 23 31	
Protection plate external	70 20 71	
Protection plate internal 107,5×51 mm	*107,5/51	
Headband	70 25 41	
Set of sweatbands	70 25 42	
Autodarkening filter SmarTlGer V9-13SQ	40 50 60	

Disclaimer Notice