

# TECHNICAL DATASHEET



www.clean-air.cz

## Filter A2B2E2K2HgP3, thread RD40x1/7"

Combined filter with RD40x1/7" thread



\* the picture is illustrational only and may vary depending on additional equipment

# TECHNICAL DATASHEET

## **Filter A2B2E2K2HgP3, thread RD40x1/7"**

Combined filter with RD40x1/7" thread



### Technical specification

Product code	50 01 66
Standards	A2B2E2K2HgP3 D R according to EN 14387 TH3 A2B2E2K2HgP R SL according to EN 12941 TM3 A2B2E2K2HgP R SL according to EN 12942
Weight	385 g
Dimensions	diameter 110 mm height 95 mm
Materials	filter housing: ABS filtration medium: microfiber glass media activated charcoal
Thread	RD40x1/7" in accordance with EN 148-1
Storage conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh
Operating conditions	+ 0°C to + 60°C, humidity 20 - 95 % Rh

Group of contaminants	Protect against
A	Organic gases and vapours with a boiling point above 65 °C (e.g. toluene, benzene, styrene, kerosene, petrol, isobutanol, ...)
B	Inorganic gases and vapours [e.g. fluorine, chlorine, hydrogen sulphide, hydrogen cyanide, hydrogen chloride, hydrogen peroxide, ...]
E	Acid gases and vapours (e.g. carbon dioxide, sulphuric acid, hydrochloric acid, formic acid, hydrogen fluoride, ...)
K	Ammonia and organic amines (e.g. methylamine, ethylamine, dimethylamine, ...)
Hg	Mercury (mercury vapours and its compounds)
P	Solid particles in the form of liquid and solid aerosols (e.g. dust, smoke, fibres, bacteria, viruses and radioactive particles, ...)
OZONE	Protection against OZONE in concentration less than 20 mg/m <sup>3</sup> (ppm) (the effectiveness tested according to Danish standard for measuring ozone, dated 26 March, 2001)

### Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.

# TECHNICAL DATASHEET

## **Filter A2B2E2K2HgP3, thread RD40x1/7"**

Combined filter with RD40x1/7" thread



### **Main requirements of EN 14387, EN 12941 and EN 12942**

<b>Breathing resistance with clean filters</b>	<b>Required</b>
30 l/min	max. 260 Pa
95 l/min	max. 980 Pa
<b>Gas filter capacity with test gas (30 l/min)</b>	<b>Required</b>
Cyclohexane C <sub>6</sub> H <sub>12</sub>	min. 35 min
Chlorine Cl <sub>2</sub>	min. 20 min
Hydrogen Sulphide H <sub>2</sub> S	min. 40 min
Hydrogen Cyanide HCN	min. 25 min
Sulphur Dioxide SO <sub>2</sub>	min. 20 min
Ammonia NH <sub>3</sub>	min. 40 min
Mercury Hg	min. 100 hour
<b>Gas filter capacity with test gas (80 l/min)</b>	<b>Required</b>
Cyclohexane C <sub>6</sub> H <sub>12</sub>	min. 70 min
Chlorine Cl <sub>2</sub>	min. 20 min
Hydrogen Sulphide H <sub>2</sub> S	min 40 min
Hydrogen Cyanide HCN	min. 25 min
Sulphur Dioxide SO <sub>2</sub>	min. 20 min
Ammonia NH <sub>3</sub>	min. 50 min
Mercury Hg	min. 100 hours
<b>Maximum permitted penetration of test aerosol (95 l/min)</b>	<b>Required</b>
Sodium Chloride NaCl	max. 0,05 %
Paraffin oil	max. 0,05 %

Filter A2B2E2K2HgP3, thread RD40x1/7" meets all requirements and comply with stated norms. In addition, in most aspects the filter extensively surpasses the requirements of the standard. For more information please contact our sales department at [export@malina-safety.cz](mailto:export@malina-safety.cz).

### **Disclaimer Notice**

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.