

Product code

71 06 00*

* add S, M or L in order to choose the size

Product description

Full face mask

Standards

EN 12942 TM3

EN 136 CL3

**Protection of respiratory tract**

In combination with CleanAIR® PAPR systems provides level of protection TM3 according to EN 12942

Weight

610 g

Product dimensions

200 mm / 180 mm / 115 mm

Visor dimensions

160 x 90 mm

Colour

black

Materials

Mask - Silicon rubber

Head harness - Natural rubber

Hose connector - ABS

Inhalation / Exhalation valve - Silicone rubber

Gasket - Silicone rubber

Headband - Polyamide

Visor - Anti-scratch coated polycarbonate

Recommended hose type

70 00 60 - Light flexi hose

Internal thread CA40x1/7" - external thread CA40x1/7"]

Lenght: seft adjusting: 600 mm - 1 100 mm / Weight: 150 g

Storage conditions

-10°C to + 55°C, humidity 20 - 80 % RH

avoid long exposure of UV radiation

Operating conditions

+10°C to + 40°C, humidity 20 - 80 % RH

Product sets / variations

product code	product description
71 06 00*	Full face mask GX02
59 16 00*	CleanAIR® Asbest including accessories (two batteries, filter, hose with holder, charger, belt, flow indicator and mask GX02)

* add S, M or L in order to choose the size

Spare parts and accessories

product code	product description
70 00 60	Light flexi hose CA40x1/7" - CA40x1/7" - straight connector
70 00 86CA	Rubber hose CA40x1/7" - CA40x1/7" - straight connector
71 06 20	Visor protection film
71 06 80	Head harness
71 06 90*	Inner mask including inner valves
71 06 95	Inhalation valve - set (membranes 5 pcs + 1 gasket)
71 06 96	Exhalation valve - set (membranes 5 pcs + 1 gasket)

* add S, M or L in order to choose the size

Compatible respiratory units

[According to EN 12942]

product code	product description	level of protection
59 00 02	CleanAIR® Asbest	TM3
51 00 00FCA	CleanAIR® Chemical 2F	TM3
52 00 00FCA	CleanAIR® Chemical 3F	TM3

Long description

The full face mask Shigematsu GX02 uses a double seal flange which provides maximal seal while keeping a high level of comfort for the wearer. The mask has a wide panoramic visor which provides a maximal visual field and a speech diaphragm which facilitates communication. The exchangeable polycarbonate visor has a special surface treatment which guarantees high scratch resistance. The mask body is made from high quality silicone which guarantees high resistance and a long operation life. The six point head harness ensures secure and easy fit. The mask is fitted with a standard connection thread RD40x1/7" according to EN 148-1 and thus enables wearers to use a wide range of canister filters and powered air purifying systems CleanAIR®. The mask is fully approved according to EN 136 and EN 12942.

Areas of application

- Chemical industry
- Laboratories
- Building industry
- Remediation operations

Limitations



- Please, read carefully relevant instruction for use and follow your national safety regulations for PPE.