# TECHNICAL DATASHEET



## Filter AerGO® A1P R SL

Combined filter with AerGO® thread



DA-057\_-\_300357\_-\_A1P\_R\_SL\_-\_EN

## TECHNICAL DATASHEET

## Filter AerGO® A1P R SL

### Combined filter with AerGO® thread



Technical specification	
Product code	30 03 57
Standards	TH3 A1P R SL according to EN 12941
Compatibility	CleanAIR® AerGO®
Weight	280 g
Dimensions	diameter 110 mm height 58 mm
Materials	filter housing: ABS filtration medium: microfiber glass media activated charcoal
Thread	TR-110 - AerGO® compatible
Storage conditions Operating conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh + 0°C to + 60°C, humidity 20 - 95 % Rh

Group of contaminants	Protect against
А	Organic gases and vapours with a boiling point above 65 °C (e.g. toluene, benzene, styrene, kerosene, petrol, isobuthanol,)
Р	Solid particles in the form of liquid and solid aerosols [e.g. dust, smoke, fibres, bacteria, viruses and radioactive particles,]

#### Disclaimer Notice

### TECHNICAL DATASHEET

## Filter AerGO® A1P R SL

### Combined filter with AerGO® thread



Main requirements of EN 12941		
Gas filter capacity with test gas (105 l/min)	Required	
Cyclohexane C6H12	min. 35 min	
Maximum permitted penetration of test aerosol (105 l/min)	Required	
Sodium Chloride NaCl	max. 0,05 %	
Paraffin oil	max. 0,05 %	

Filter AerGO® A1P R SL meets all requiremets and comply with stated norms. In addition, in most aspects the filter extensively surpasses the requirements of the standard. For more information please contact our sales department at export@malina-safety.cz.

#### Disclaimer Notice